

Intercom Bench Top Vacuum Packers



Square 400-B

Overall dimensions	510x560x460H
Vacuum chamber	410x450x220H
Sealing bar	mm 400 (1x5 mm)
Vacuum Pump	25 m3/h
Control panel	Digit 6 PRG
Voltage	230 V/50 Hz

Square 450-B

Overall dimensions	560x610x460H
Vacuum chamber	460x500x220H
Sealing bar	mm 450 (1x5 mm)
Vacuum Pump	25 m3/h
Control panel	Digit 6 PRG
Voltage	230 V/50 Hz



Square 450-BIS-B

Overall dimensions	600x560x460H
Vacuum chamber	500x460x220H
Sealing bar	mm 450 (2x5 mm)
Vacuum Pump	Q = 25 m3/h OIL
Control panel	Digit 6 PRG
Voltage	230 V/50 Hz

2 seal bars on left and right side of chamber

Standard Features and Benefits

- 6 program multifunction digital panel
Saves time with pre-set functions and easy to use
- Stainless Steel Construction
Hard wearing and looks good
- Auto cleaning oil system
Less servicing needs
- Electronic soft vacuum
Will not damage delicate items
- Removable sealing bars
Easy to clean and replace
- Polyethylene infill plates
Faster cycle time on smaller packs
- Easy access to internals including
Easy to service and replace parts

Optional Extras

- Docket Printer
- Busch Pump
Higher capacity pump
- Extra Sealing Bar
Seal more per cycle
- Option for gas
Food stays fresher longer
- Lid Hook
- Inclined plane for liquids
Vacuum pack any liquids

D&L Packaging
Unit D 237 Bush Road Albany Auckland
Tel: (09) 443 6301 Fax: (09) 443 6307
Email: info@dlpack.co.nz Web: www.dlpack.co.nz